



Product:	Super-Mat 2	Standard widths with borders:	85 cm, 115 cm and 150 cm
Customs tariff number:	57032999	Standard widths without borders:	3 cm smaller than for mats with borders (e.g. 82 cm)
Product details:	<ul style="list-style-type: none"> » Made of Econyl® regenerated nylon which is made entirely from ocean and landfill waste » Dual performance - scrape and wipe » Skid resistant rubber back » Light- and colour resistant » PVC-free » Suitable for underfloor heating » 5 year Manufacturers Guarantee* » 11 year warranty against significant colour loss » Made in Europe 	Standard lengths:	all lengths up to 700 cm
Burning behaviour:	EN 13501-1 / Cf1-s1	Colouration:	Solution dyed
Static electrical propensity:	EN 14041 Antistatic	Pile:	100 % Econyl® regenerated nylon
Slip resistance:	NFSI High-Traction	Pile height:	approx. 9 mm
Total mat weight:	3.10 kg/sqm	Pile weight:	without substrate: 800 g/sqm with substrate: 900 g/sqm
Overall height:	approx. 10 mm	Backing:	100 % Nitrile rubber Available with kleeeted or smooth backing
Dirt absorption:	950 g/sqm	Rubber thickness:	1.80 mm
Moisture absorption:	3 - 4 l/sqm	Rubber weight:	2.20 kg/sqm
Application areas:	<ul style="list-style-type: none"> » Heavy traffic areas » Busy entrances 	Border width:	20 mm Available with or without borders
		Border thickness:	2.80 mm
		Cleaning:	Washable up to 60 °C » Tumble dry up to 60 °C

Colours:

