gdmats@gdmats.eu www.gdmats.eu

GD - Forklift Mat

All products are protected with coppyright



Technical Datasheet





Customs tariff number:

Static electrical propensity:

Total mat weight:

Overall height:

Dirt absorption:

Application areas:

Moisture absorption:

Product details:











Forklift Mat

57032098

wheels

and stability

» Made in Europe

EN 14041 Antistatic

» PVC-free

5.02 kg/sqm

1100 g/sqm

5 - 6 l/sqm

approx. 16 mm

» Dispatch area » Loading bay

» Warehouse

» Removes dirt and moisture from forklift

» Highly absorbent and durable surface » Extra thick rubber backing for strength

» Suitable for underfloor heating

» Reduces the risk of slips due to a wet floor » Savings on cleaning costs and time



Standard widths without borders:

Standard lengths:

Colouration:

Pile:

Pile height: Pile weight:

Backing:

Rubber thickness: Rubber weight: Border width:

Border thickness:

Cleaning:

85 cm, 115 cm, 150 cm and 200 cm

3 cm smaller than for mats with borders (e.g. 82 cm)

123

all lengths up to 700 cm

Solution dyed

a combination of Micro Nylon and High-Twist Nylon (HTN) Polyamide 6 (Sustainable yarn made from 50 % post

industrial waste) approx. 14 mm

without substrate: 1000 g/sqm with substrate: 1100 g/sqm

100 % Nitrile rubber Smooth backing 2.80 mm

3.92 kg/sqm 20 mm

Available with or without borders 3.80 mm

» Carpet cleaning / Vacuum cleaners

» Non-washable

Colour:

